LAMPTUB 60 SURF. CEILING ROSE



L61SS084MOTE930D3

LTUB60 SU SF 840 2200 9WW TECH DA WE



Description:

extrusion, with circular section of 60mm and length 840 mm, with matt black reflector ULTRA COMFORT and optics for light distribution control and low glare UGR<16. Model for MID-POWER LED, with colour temperature 3000K and CRI90. Built-in electronic DALI wiring. With IP20, IK07 degree of protection. Insulation class I/II. Photobiological safety group 0. Lifetime:50000 L90 B10 Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.""" "



Finish: Palette WELLBEING - 3 TEXTURED

840 x 67 x 80 mm Dimensions:

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output: 1.260 lm °K: 3000 Plum: 13,7W CRI: 90 Efficacy: 92 lm/w 61 R9: UGR: MacAdam: 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz LED Lifetime: 50.000 L90 B10 (Ta=25°C) Gear: Adjustable DALI

Power:

Light output tolerance +/- 10%

CUSTOM MADE OPTIONS:



















LAMPTUB 60 SURF. CEILING ROSE





L61SS084MOTE930D3


LTUB60 SU SF 840 2200 9WW TECH DA WE


PHOTOMETRIC DATA:


L61SS084MOTE930D3 η = 100% lmax = 1305 cd/klmUTE: CIE: 98 100 100 100 100

















LAMPTUB 60 SURF. CEILING ROSE



ACCESORIES:

Assembly



Product code:

L6SUECB



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW



LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.