LAMPTUB 60 SURF. CEILING ROSE

L61SS084MOTE930NB

LTUB60 SU SF 840 2200 9WW TECH BK

Matte black RAL 9011

840 x 67 x 80 mm

Description:

Finish:

Dimensions:

""""""Surface-mounted luminaire, model LAMPTUB 60 TECH by LAMP. Made of 80% recycled aluminium extrusion, with circular section of 60mm and length 840 mm, with matt black reflector ULTRA COMFORT and optics for light distribution control and low glare UGR<16. Model for MID-POWER LED, with colour temperature 3000K and CRI90. Built-in electronic wiring. With IP20, IK07 degree of protection. Insulation class I/II. Photobiological safety group 0. Lifetime:50000 L90 B10 Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.""" "



Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output:	1.260 lm	⁰K :	3000
Plum:	13,7W	CRI :	90
Efficacy:	92 lm/w	R9 :	61
UGR:	<16	MacAdam:	3
Туре:	MID POWER LED	Power Supply:	220-240V 50/60Hz
LED Lifetime:	50.000 L90 B10 (Ta=25⁰C)	Gear:	Electronic
Power:	11W		

Light output tolerance +/- 10%

CUSTOM MADE OPTIONS:



Worktitude for light


LAMPTUB 60 SURF. CEILING ROSE


L61SS084MOTE930NB

LTUB60 SU SF 840 2200 9WW TECH BK



PHOTOMETRIC DATA :





LAMPTUB 60 SURF. CEILING ROSE

ACCESORIES :

Assembly



Product code: L6SUECB

Description: LTUB60 ACC. SUR END COVER BK.



Product code: L6SUECW

Description: LTUB60 ACC. SUR END COVER WH.

Worktitude for light



Product code: L6SUECW3

Description: LTUB60 ACC. SUR END COVER WE.



Product code: L6SUECW4

Description: LTUB60 ACC. SUR END COVER BS.