

LAMPTUB 60 SURF. CEILING ROSE



L61SS112LOOC930D3





Description:

Surface mounted luminaire Lamptub 60 from LAMP. Made of recycled aluminium extrusion with circular section of 60mm and length of 1120mm, an opal comfort diffuser made of a translucent polycarbonate diffuser and an optical film to achieve a controlled light distribution and low UGR<19. Model for MID-POWER LED, with colour temperature 3000K with CRI90. Built-in electronic DALI control gear. With IP40, IK07 degree of protection. Insulation class I / II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.



Finish: Palette WELLBEING - 3 TEXTURED

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output: 930 lm °K: 3000 Plum: 12,9W CRI: 90 Efficacy: 72,1 lm/w 64 R9: UGR: <19 MacAdam: 3

 Type:
 MID POWER LED
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 72.000 L80 B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 10.6W

Light output tolerance +/- 10%



CLASE

















CUSTOM MADE OPTIONS:



















LAMPTUB 60 SURF. CEILING ROSE




L61SS112LOOC930D3


LTUB60 SU SF 1120 1700 WW COMF DALI WE


PHOTOMETRIC DATA:


L61SS112LOOC930N3 η = 100% Imax = 665 cd/klm UTE: 1,00C


CIE: 66 90 99 100 100


















LAMPTUB 60 SURF. CEILING ROSE



ACCESORIES:

Assembly



Product code:

L6SUECB L



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW

Description:

LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.