## LAMPTUB 60 SURF. CEILING ROSE



## L61SS112LOOP940N3




## LTUB60 SU SF 1120 1800 NW OPAL WE

## Description:

Surface mounted luminaire Lamptub 60 from LAMP. Made of recycled aluminium extrusion with circular section of 60mm and length of 1120mm, with opal polycarbonate diffuser. Model for MID-POWER LED, with colour temperature 4000K with CRI90. Built-in electronic ON/OFF control gear. With IP40, IK07 degree of protection. Insulation class I / II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.

Palette WELLBEING - 3 TEXTURED Finish:



Installation: Suspended

## **TECHNICAL SPECIFICATIONS:**

Light output: 1.037 lm °K: 4000 Plum: 12,9W CRI: 90 Efficacy: 80,4 lm/w R9: 70 Type: MID POWER LED MacAdam: 3

LED Lifetime: 72.000 L80 B10 (Ta=25°C) Power Supply: 220-240V 50/60Hz

Gear: Power: 10.6W Electronic

## Light output tolerance +/- 10%



CLASE









































Data according to regulations 2019/2020/EU and 2019/2015/EU













## LAMPTUB 60 SURF. CEILING ROSE





L61SS112LOOP940N3


LTUB60 SU SF 1120 1800 NW OPAL WE


## **PHOTOMETRIC DATA:**


L61SS112LOOP940N3 η = 100% Imax = 390 cd/klm UTE: 1,00E + 0,00T CIE: 50 81 97 100 100
















Data according to regulations 2019/2020/EU and 2019/2015/EU

## LAMPTUB 60 SURF. CEILING ROSE



# ACCESORIES:

## **Assembly**



Product code:

L6SUECB



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW

Description:

LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.