### LAMPTUB 60 SURF. CEILING ROSE



#### L61SS112MOOC927N4

# LTUB60 SU SF 1120 3200 VWW COMF BS

#### Description:

Surface mounted luminaire Lamptub 60 from LAMP. Made of recycled aluminium extrusion with circular section of 60mm and length of 1120mm, an opal comfort diffuser made of a translucent polycarbonate diffuser and an optical film to achieve a controlled light distribution and low UGR<19. Model for MID-POWER LED, with colour temperature 2700K with CRI90. Built-in electronic ON/OFF control gear. With IP40, IK07 degree of protection. Insulation class I / II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.



Finish: Palette BE SOCIAL - 4 TEXTURED

Installation: Suspended

# **TECHNICAL SPECIFICATIONS:**

Light output: 1.811 lm °K: 2700 Plum: 25,4W CRI: 90 Efficacy: 71,3 lm/w R9: 57 UGR: <19 MacAdam: 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 72.000 L80 B10 (Ta=25°C) Gear: Electronic

Power:

# Light output tolerance +/- 10%



CLASE



























### **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU











Pág. 1/3

# LAMPTUB 60 SURF. CEILING ROSE





L61SS112MOOC927N4


# LTUB60 SU SF 1120 3200 VWW COMF BS


### **PHOTOMETRIC DATA:**


L61SS112MOOC927N4  $\eta$  = 100% Imax = 663 cd/klm Imax = 1,00C Imax = 66 90 99 100 100
















# **LAMPTUB 60 SURF. CEILING ROSE**



# ACCESORIES:

# Assembly



Product code:

L6SUECB L



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW

Description:

LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.