
LAMPTUB 60 SURF. CEILING ROSE



L61SS112MOOC9TWD3

LTUB60 SU SF 1120 3300 TW COMF DALI WE



Description:

Surface mounted luminaire Lamptub 60 from LAMP. Made of recycled aluminium extrusion with circular section of 60mm and length of 1120mm, an opal comfort diffuser made of a translucent polycarbonate diffuser and an optical film to achieve a controlled light distribution and low UGR<19. Model for MID-POWER LED, with TW colour temperature with CRI90. Built-in electronic DALI control gear. With IP40, IK07 degree of protection. Insulation class I / II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.



Finish: Palette WELLBEING - 3 TEXTURED

1.127 x 67 x 80 mm Dimensions:

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output: 1.863 lm °K: TW Plum: 22W CRI: 90 Efficacy: 84,7 lm/w 3 MacAdam:

UGR: <19 Power Supply: 220-240V 50/60Hz

Type: MID POWER LED Gear: Adjustable DALI DT8

LED Lifetime: 50.000 L80 B10 (Ta=25°C)

18.5W Power:

Light output tolerance +/- 10%



CLASE

























CUSTOM MADE OPTIONS:



















Data according to regulations 2019/2020/EU and 2019/2015/EU

LAMPTUB 60 SURF. CEILING ROSE



L61SS112MOOC9TWD3


LTUB60 SU SF 1120 3300 TW COMF DALI WE


PHOTOMETRIC DATA:


L61SS112MOOC9TWD3 η = 100% Imax = 663 cd/klm UTE: 1,00C


CIE: 66 90 99 100 100




















LAMPTUB 60 SURF. CEILING ROSE



ACCESORIES:

Assembly



Product code:

L6SUECB



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW



LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.