# LAMPTUB 60 SURF. CEILING ROSE

#### L61SS112MOTE930DW




#### LTUB60 SU SF 1120 2960 9WW TECH DA WH

#### **Description:**

Surface-mounted luminaire, model LAMPTUB 60 TECH by LAMP. Made of 80% recycled aluminium extrusion, with circular section of 60mm and length 1120 mm, with matt black reflector ULTRA COMFORT and optics for light distribution control and low glare UGR<16. Model for MID-POWER LED, with colour temperature 3000K and CRI90. Built-in electronic DALI wiring. With IP20, IK07 degree of protection. Insulation class I/II. Photobiological safety group 0. Lifetime:50000 L90 B10 Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.

Finish: Matte white RAL 9010

Dimensions: 1.120 x 67 x 80 mm



Installation: Suspended

#### **TECHNICAL SPECIFICATIONS:**

Light output:	1.680 lm	٩ <b>κ</b> :	3000
Plum:	17,8W	CRI :	90
Efficacy:	94,4 lm/w	R9 :	61
UGR:	<16	MacAdam:	3
Туре:	MID POWER LED	Power Supply:	220-240V 50/60Hz
LED Lifetime:	50.000 L90 B10 (Ta=25°C)	Gear:	Adjustable DALI
Power:	14W		

#### Light output tolerance +/- 10%



### **CUSTOM MADE OPTIONS:**



Worktitude for light

## LAMPTUB 60 SURF. CEILING ROSE


L61SS112MOTE930DW


LTUB60 SU SF 1120 2960 9WW TECH DA WH



Worktitude for light

#### PHOTOMETRIC DATA :





## LAMPTUB 60 SURF. CEILING ROSE

## ACCESORIES :

### Assembly



Product code: L6SUECB

Description: LTUB60 ACC. SUR END COVER BK.



Product code: L6SUECW

Description: LTUB60 ACC. SUR END COVER WH.

Worktitude for light



Product code: L6SUECW3

Description: LTUB60 ACC. SUR END COVER WE.



Product code: L6SUECW4

Description: LTUB60 ACC. SUR END COVER BS.