LAMPTUB 60 SURF. CEILING ROSE



L61SS112MOTE940DW




LTUB60 SU SF 1120 2960 9NW TECH DA WH

Description:

Surface-mounted luminaire, model LAMPTUB 60 TECH by LAMP. Made of 80% recycled aluminium extrusion, with circular section of 60mm and length 1120 mm, with matt black reflector ULTRA COMFORT and optics for light distribution control and low glare UGR<16. Model for MID-POWER LED, with colour temperature 4000K and CRI90. Built-in electronic DALI wiring. With IP20, IK07 degree of protection. Insulation class I/II. Photobiological safety group 0. Lifetime:50000 L90 B10 Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.

Finish: Matte white RAL 9010 1.120 x 67 x 80 mm Dimensions:



Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output: 1.760 lm °K: 4000 Plum: 17,8W CRI: 90 Efficacy: 98,9 lm/w R9: 85 UGR: MacAdam: 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz LED Lifetime: 50.000 L90 B10 (Ta=25°C) Gear: Adjustable DALI

14W Power:

Light output tolerance +/- 10%

























Data according to regulations 2019/2020/EU and 2019/2015/EU













LAMPTUB 60 SURF. CEILING ROSE




L61SS112MOTE940DW


LTUB60 SU SF 1120 2960 9NW TECH DA WH


PHOTOMETRIC DATA:


L61SS112MOTE940DW η = 100% Imax = 1333 cd/klm UTE:


CIE: 98 100 100 100 100




















LAMPTUB 60 SURF. CEILING ROSE



ACCESORIES:

Assembly



Product code:

L6SUECB



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW

Description:

LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.