LAMPTUB 60 SURF. CEILING ROSE



L61SS168MOTE930DW



LTUB60 SU SF 1680 4400 9WW TECH DA WH

Description:

Surface-mounted luminaire, model LAMPTUB 60 TECH by LAMP. Made of 80% recycled aluminium extrusion, with circular section of 60mm and length 1680mm, with matt black reflector ULTRA COMFORT and optics for light distribution control and low glare UGR<16. Model for MID-POWER LED, with colour temperature 3000K and CRI90. Built-in electronic DALI wiring. With IP20, IK07 degree of protection. Insulation class I/II. Photobiological safety group 0. Lifetime:50000 L90 B10 Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.



Finish: Matte white RAL 9010 1.680 x 67 x 80 mm Dimensions:

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output: 2.520 lm °K: 3000 Plum: 26,7W CRI: 90 Efficacy: 94,4 lm/w 61 R9: UGR: MacAdam: 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz LED Lifetime: 50.000 L90 B10 (Ta=25°C) Gear: Adjustable DALI

22W Power:

Light output tolerance +/- 10%



CLASE

























CUSTOM MADE OPTIONS:



















LAMPTUB 60 SURF. CEILING ROSE





L61SS168MOTE930DW


LTUB60 SU SF 1680 4400 9WW TECH DA WH


PHOTOMETRIC DATA:


L61SS168MOTE930DW η = 100% lmax = 1305 cd/klmUTE: CIE: 98 100 100 100 100

















LAMPTUB 60 SURF. CEILING ROSE



ACCESORIES:

Assembly



Product code:

L6SUECB



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW



LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.