LAMPTUB 60 SURF. CEILING ROSE



L61SS168MOTE940N4

- LTUB60 SU SF 1680 4400 9NW TECH BS

Description:

"""""Surface-mounted luminaire, model LAMPTUB 60 TECH by LAMP. Made of 80% recycled aluminium extrusion, with circular section of 60mm and length 1680mm, with matt black reflector ULTRA COMFORT and optics for light distribution control and low glare UGR<16. Model for MID-POWER LED, with colour temperature 4000K and CRI90. Built-in electronic wiring. With IP20, IK07 degree of protection. Insulation class I/II. Photobiological safety group 0. Lifetime:50000 L90 B10 Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.""" "



Finish: Palette BE SOCIAL - 4 TEXTURED

Dimensions: 1.680 x 67 x 80 mm

Installation: Suspended

TECHNICAL SPECIFICATIONS:

 Light output:
 2.640 lm
 °K:
 4000

 Plum:
 26,7W
 CRI:
 90

 Efficacy:
 98,9 lm/w
 R9:
 85

 UGR:
 <16</td>
 MacAdam:
 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L90 B10 (Ta=25°C) Gear: Electronic

Power: 22W

Light output tolerance +/- 10%

CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU











LAMPTUB 60 SURF. CEILING ROSE





L61SS168MOTE940N4


LTUB60 SU SF 1680 4400 9NW TECH BS


PHOTOMETRIC DATA:


L61SS168MOTE940N4 η = 100% lmax = 1333 cd/klm UTE: CIE: 98 100 100 100 100

















LAMPTUB 60 SURF. CEILING ROSE



ACCESORIES:

Assembly



Product code:

L6SUECB



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW



LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.