### LAMPTUB 60 SUSPENDED TRACK



### L61ST084LOOC930NW




### **LTUB60 SUT 840 1300 WW COMF WH**

### Description:

Lamptub 60 model from LAMP to be installed on a suspended rail. Made of recycled aluminium extrusion with circular section of 60mm and length of 840mm, an opal comfort diffuser made of a translucent polycarbonate diffuser and an optical film to achieve a controlled light distribution and low UGR<19. Model for MID-POWER LED, with colour temperature 3000K with CRI90. Built-in electronic ON/OFF control gear. With IP20, IK07 degree of protection. Insulation class II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.

Finish: Matte white RAL 9010

Dimensions: 847 x 67 x 80 mm Weight: 2.110 g



# Installation: 3-Circuit track

### **TECHNICAL SPECIFICATIONS:**

Light output: 698 lm °K: 3000 Plum: 10W CRI: 90 Efficacy: 69,8 lm/w 64 R9: UGR: <19 MacAdam: 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 72.000 L80 B10 (Ta=25°C) Gear: Electronic

8.5W Power:

# Light output tolerance +/- 10%

































## **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU













# **LAMPTUB 60 SUSPENDED TRACK**




L61ST084LOOC930NW


# **LTUB60 SUT 840 1300 WW COMF WH**


### **PHOTOMETRIC DATA:**


L61ST084LOOC930NW  $\eta$  = 100% Imax = 665 cd/klm UTE: 1,00C


CIE: 66 90 99 100 100



















# **LAMPTUB 60 SUSPENDED TRACK**



# ACCESORIES:

# **Assembly**



Product code:

L6SUECB



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW



LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.