## **LAMPTUB 60 SUSPENDED TRACK**



### L61ST084LOOP930N3



### **LTUB60 SUT 840 1300 WW OPAL WE**

### Description:

Lamptub 60 model from LAMP to be installed on a suspended rail. Made of recycled aluminium extrusion with circular section of 60mm and length of 840mm, with opal polycarbonate diffuser. Model for MID-POWER LED, with colour temperature 3000K with CRI90. Built-in electronic ON/OFF control gear. With IP20, IK07 degree of protection. Insulation class II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.



Finish: Palette WELLBEING - 3 TEXTURED

847 x 67 x 80 mm Dimensions: Weight: 2.110 g

Installation: 3-Circuit track

### **TECHNICAL SPECIFICATIONS:**

Light output: 754 lm °K: 3000 Plum: 10W CRI: 90 Efficacy: 75,4 lm/w 64 R9: Type: MID POWER LED MacAdam: 3

LED Lifetime: 72.000 L80 B10 (Ta=25°C) Power Supply: 220-240V 50/60Hz

Gear: Power: 8.5W Electronic

# Light output tolerance +/- 10%































# **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU











# **LAMPTUB 60 SUSPENDED TRACK**





L61ST084LOOP930N3


# **LTUB60 SUT 840 1300 WW OPAL WE**


# **PHOTOMETRIC DATA:**


L61ST084LOOP930N3  $\eta$  = 100% lmax = 390 cd/klmUTE: 1,00E + 0,00T CIE: 50 81 97 100 100
















# **LAMPTUB 60 SUSPENDED TRACK**



# ACCESORIES:

# **Assembly**



Product code:

L6SUECB



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW



LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.