LAMPTUB 60 SUSPENDED TRACK



L61ST084MOIP9TWDW

LTUB60 SUT 840 3400 TW D/I COMF DALI WH



Description:

Lamptub 60 model from LAMP to be installed on a suspended rail. Made of recycled aluminium extrusion with circular section of 60mm and length of 840mm. Direct-indirect light model with an opal comfort diffuser made of a translucent polycarbonate diffuser and an optical film to achieve a controlled light distribution and low UGR<19. Model for MID-POWER LED, with TW colour temperature with CRI90. Built-in electronic DALI control gear. With IP20, IK07 degree of protection. Insulation class II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.



Finish: Matte white RAL 9010

Dimensions: 847 x 67 x 80 mm Weight: 2.290 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output: 2.128 lm °K: TW Plum: 27,4W CRI: 90 Efficacy: 77,7 lm/w 3 MacAdam:

UGR: Power Supply: 220-240V 50/60Hz

Type: MID POWER LED Gear:

LED Lifetime: 50.000 L80 B10 (Ta=25°C)

24.7W Power:

Light output tolerance +/- 10%

































Adjustable DALI DT8

CUSTOM MADE OPTIONS:















LAMPTUB 60 SUSPENDED TRACK





L61ST084MOIP9TWDW


LTUB60 SUT 840 3400 TW D/I COMF DALI WH


PHOTOMETRIC DATA:


L61ST084MOIP9TWDW η = 100% lmax = 453 cd/klmUTE: 0,69C + 0,32T CIE: 66 90 99 68 100

















LAMPTUB 60 SUSPENDED TRACK



ACCESORIES:

Assembly



Product code:

L6SUECB



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW



LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.