#### LAMPTUB 60 SUSPENDED TRACK



#### L61ST084MOOC927N4

# **LTUB60 SUT 840 2400 VWW COMF BS** Description:



Lamptub 60 model from LAMP to be installed on a suspended rail. Made of recycled aluminium extrusion with circular section of 60mm and length of 840mm, an opal comfort diffuser made of a translucent polycarbonate diffuser and an optical film to achieve a controlled light distribution and low UGR<19. Model for MID-POWER LED, with colour temperature 2700K with CRI90. Built-in electronic ON/OFF control gear. With IP20, IK07 degree of protection. Insulation class II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.



Finish: Palette BE SOCIAL - 4 TEXTURED

847 x 67 x 80 mm Dimensions: Weight: 2.110 g

Installation: 3-Circuit track

#### **TECHNICAL SPECIFICATIONS:**

Light output: 1.359 lm °K: 2700 Plum: 17,4W CRI: 90 Efficacy: 78,1 lm/w R9: 57 UGR: MacAdam: 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 72.000 L80 B10 (Ta=25°C) Gear: Electronic

Power:

# Light output tolerance +/- 10%





























# **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU











#### **LAMPTUB 60 SUSPENDED TRACK**





L61ST084MOOC927N4


### **LTUB60 SUT 840 2400 VWW COMF BS**


#### **PHOTOMETRIC DATA:**


L61ST084MOOC927N4  $\eta$  = 100% Imax = 663 cd/klm UTE: 1,00C




















## **LAMPTUB 60 SUSPENDED TRACK**



# ACCESORIES:

## Assembly



Product code:

L6SUECB



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW



LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.