
LAMPTUB 60 SUSPENDED TRACK



L61ST084MOOP940N3

- LTUB60 SUT 840 2600 NW OPAL WE



Description:

Lamptub 60 model from LAMP to be installed on a suspended rail. Made of recycled aluminium extrusion with circular section of 60mm and length of 840mm, with opal polycarbonate diffuser. Model for MID-POWER LED, with colour temperature 4000K with CRI90. Built-in electronic ON/OFF control gear. With IP20, IK07 degree of protection. Insulation class II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.



Finish: Palette WELLBEING - 3 TEXTURED

Dimensions: 847 x 67 x 80 mm **Weight:** 2.110 g

Installation: 3-Circuit track

TECHNICAL SPECIFICATIONS:

Light output: 1.594 lm °K: 4000 Plum: 17,4W CRI: 90 Efficacy: 91,6 lm/w 70 R9: Type: MID POWER LED MacAdam: 3

LED Lifetime: 72.000 L80 B10 (Ta=25°C) **Power Supply:** 220-240V 50/60Hz

Power: 15.1W Gear: Electronic

Light output tolerance +/- 10%























CUSTOM MADE OPTIONS:



















LAMPTUB 60 SUSPENDED TRACK





L61ST084MOOP940N3


LTUB60 SUT 840 2600 NW OPAL WE


PHOTOMETRIC DATA:


L61ST084MOOP940N3 η = 100% lmax = 390 cd/klmUTE: 1,00E + 0,00T CIE: 50 81 97 100 100
















LAMPTUB 60 SUSPENDED TRACK



ACCESORIES:

Assembly



Product code:

L6SUECB



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW



LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.