LAMPTUB 60 SUSPENDED TRACK




L61ST112MOTE940NW



LTUB60 SUT 1120 2960 9NW TECH WH

Description:

Luminaire to be installed on a suspended rail, model LAMPTUB 60 TECH by LAMP. Made of 80% recycled aluminium extrusion, with circular section of 60mm and length 1120 mm, with matt black reflector ULTRA COMFORT and optics for light distribution control and low glare UGR<16. Model for MID-POWER LED, with colour temperature 4000K and CRI90. Built-in electronic wiring. With IP20, IK07 degree of protection. Insulation class II. Photobiological safety group 0. Lifetime:50000 L90 B10 Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette. Compatible with Lamp Nomadic system.



Finish: Matte white RAL 9010 1.120 x 67 x 80 mm Dimensions:

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output: 1.760 lm °K: 4000 Plum: 17,8W CRI: 90 Efficacy: 98,9 lm/w R9: 85 UGR: MacAdam: 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L90 B10 (Ta=25°C) Gear: Electronic

14W Power:

Light output tolerance +/- 10%





































Data according to regulations 2019/2020/EU and 2019/2015/EU















LAMPTUB 60 SUSPENDED TRACK



L61ST112MOTE940NW


LTUB60 SUT 1120 2960 9NW TECH WH


PHOTOMETRIC DATA:


L61ST112MOTE940NW η = 100% Imax = 1333 cd/klm UTE:


CIE: 98 100 100 100 100




















LAMPTUB 60 SUSPENDED TRACK



ACCESORIES:

Assembly



Product code:

L6SUECB



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW



LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.