
LAMPTUB 60 SURFACE TRACK



L61TK084LOOC940N3

LTUB60 TRACK 220 840 1300 NW COMF WE



Description:

Lamptub 60 model from LAMP to be installed on a surface-mounted rail. Made of recycled aluminium extrusion with circular section of 60mm and length of 840mm, an opal comfort diffuser made of a translucent polycarbonate diffuser and an optical film to achieve a controlled light distribution and low UGR<19. Model for MID-POWER LED, with colour temperature 4000K with CRI90. Built-in electronic ON/OFF control gear. With IP20, IK07 degree of protection. Insulation class II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.



Finish: Palette WELLBEING - 3 TEXTURED

847 x 67 x 112 mm Dimensions: Weight: 2.030 g

Installation: 3-Circuit track

TECHNICAL SPECIFICATIONS:

Light output: 720 lm °K: 4000 Plum: 10W CRI: 90 Efficacy: 72 lm/w 70 R9: UGR: <19 MacAdam: 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L90 B10 (Ta=25°C) Gear: Electronic

8.5W Power:

Light output tolerance +/- 10%































CUSTOM MADE OPTIONS:



















LAMPTUB 60 SURFACE TRACK




L61TK084LOOC940N3


LTUB60 TRACK 220 840 1300 NW COMF WE


PHOTOMETRIC DATA:


L61TK084LOOC940N3 η = 100% Imax = 665 cd/klm UTE: 1,00C


CIE: 66 90 99 100 100




















LAMPTUB 60 SURFACE TRACK



ACCESORIES:

Assembly



Product code:

L6SUECB



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW



LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.