LAMPTUB 60 SURFACE TRACK

L61TK084LOOP927NB


LTUB60 TRACK 220 840 1300 VWW OPAL BK

Description:

Lamptub 60 model from LAMP to be installed on a surface-mounted rail. Made of recycled aluminium extrusion with circular section of 60mm and length of 840mm, with opal polycarbonate diffuser. Model for MID-POWER LED, with colour temperature 2700K with CRI90. Built-in electronic ON/OFF control gear. With IP20, IK07 degree of protection. Insulation class II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.

Finish:Matte black RAL 9011Dimensions:847 x 67 x 112 mm

Weight: 2.030 g




Installation: 3-Circuit track

TECHNICAL SPECIFICATIONS:

Light output:	717 lm	⁰К:	2700
Plum:	10W	CRI :	90
Efficacy:	71,7 lm/w	R9 :	57
Туре:	MID POWER LED	MacAdam:	3
LED Lifetime:	50.000 L90 B10 (Ta=25ºC)	Power Supply:	220-240V 50/60Hz
Power:	8.5W	Gear:	Electronic

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es Worktitude for light


LAMPTUB 60 SURFACE TRACK


L61TK084LOOP927NB

LTUB60 TRACK 220 840 1300 VWW OPAL BK



PHOTOMETRIC DATA :





LAMPTUB 60 SURFACE TRACK

ACCESORIES :

Assembly



Product code: L6SUECB

Description: LTUB60 ACC. SUR END COVER BK.



Product code: L6SUECW

Description: LTUB60 ACC. SUR END COVER WH.

Worktitude for light



Product code: L6SUECW3

Description: LTUB60 ACC. SUR END COVER WE. Product code:

L6SUECW4

Description: LTUB60 ACC. SUR END COVER BS.