
### **LAMPTUB 60 SURFACE TRACK**



### L61TK084MOOP930N3

LTUB60 TRACK 220 840 2500 WW OPAL WE




### Description:

Lamptub 60 model from LAMP to be installed on a surface-mounted rail. Made of recycled aluminium extrusion with circular section of 60mm and length of 840mm, with opal polycarbonate diffuser. Model for MID-POWER LED, with colour temperature 3000K with CRI90. Built-in electronic ON/OFF control gear. With IP20, IK07 degree of protection. Insulation class II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.

Finish: Palette WELLBEING - 3 TEXTURED

847 x 67 x 112 mm Dimensions: Weight: 2.030 g



# Installation: 3-Circuit track

### **TECHNICAL SPECIFICATIONS:**

Light output: 1.545 lm °K: 3000 Plum: 17,4W CRI: 90 Efficacy: 88,8 lm/w 64 R9: Type: MID POWER LED MacAdam: 3

LED Lifetime: 50.000 L90 B10 (Ta=25°C) Power Supply: 220-240V 50/60Hz

Gear: Power: 15.1W Electronic

## Light output tolerance +/- 10%















## **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU













## **LAMPTUB 60 SURFACE TRACK**





**L61TK084MOOP930N3** 


## LTUB60 TRACK 220 840 2500 WW OPAL WE


### **PHOTOMETRIC DATA:**


L61TK084MOOP930N3  $\eta$  = 100% lmax = 390 cd/klmUTE: 1,00E + 0,00T CIE: 50 81 97 100 100















## **LAMPTUB 60 SURFACE TRACK**



# ACCESORIES:

# Assembly



Product code:

L6SUECB



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW



LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.