## **LAMPTUB 60 SURFACE TRACK**



## L61TK112LOOP927NB



## LTUB60 TRACK 220 1120 1700 VWW OPAL BK

## Description:

Lamptub 60 model from LAMP to be installed on a surface-mounted rail. Made of recycled aluminium extrusion with circular section of 60mm and length of 1120mm, with opal polycarbonate diffuser. Model for MID-POWER LED, with colour temperature 2700K with CRI90. Built-in electronic ON/OFF control gear. With IP20, IK07 degree of protection. Insulation class II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.

Finish: Matte black RAL 9011

1.127 x 67 x 112 mm Dimensions: Weight: 2.580 g



## Installation: Suspended

## **TECHNICAL SPECIFICATIONS:**

Light output: 955 lm °K: 2700 Plum: 12,5W CRI: 90 Efficacy: 76,4 lm/w R9: 57 Type: MID POWER LED MacAdam: 3

LED Lifetime: 50.000 L90 B10 (Ta=25°C) Power Supply: 220-240V 50/60Hz

Gear: Power: 10.6W Electronic

#### Light output tolerance +/- 10%

















# **CUSTOM MADE OPTIONS:**











Data according to regulations 2019/2020/EU and 2019/2015/EU













## **LAMPTUB 60 SURFACE TRACK**





L61TK112LOOP927NB


## LTUB60 TRACK 220 1120 1700 VWW OPAL BK


## **PHOTOMETRIC DATA:**


L61TK112LOOP927NB  $\eta$  = 100% lmax = 390 cd/klmUTE: 1,00E + 0,00T CIE: 50 81 97 100 100

















## **LAMPTUB 60 SURFACE TRACK**



# ACCESORIES:

## Assembly



Product code:

L6SUECB



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW



LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.