### **LAMPTUB 60 SURFACE TRACK**



### L61TK112MOOP940D4

### LTUB60 TRACK 220 1120 3500 NW OPAL DA BS



### Description:

Lamptub 60 model from LAMP to be installed on a surface-mounted rail. Made of recycled aluminium extrusion with circular section of 60mm and length of 1120mm, with opal polycarbonate diffuser. Model for MID-POWER LED, with colour temperature 4000K with CRI90. Built-in electronic DALI control gear. With IP20, IK07 degree of protection. Insulation class II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.



Finish: Palette BE SOCIAL - 4 TEXTURED

1.127 x 67 x 112 mm Dimensions: Weight: 2.580 g

Installation: 3-Circuit track

### **TECHNICAL SPECIFICATIONS:**

Light output: 2.126 lm °K: 4000 Plum: 24,6W CRI: 90 Efficacy: 86,4 lm/w 70 R9: Type: MID POWER LED MacAdam: 3

LED Lifetime: 50.000 L90 B10 (Ta=25°C) Power Supply: 220-240V 50/60Hz Gear: Power: 21.6W Adjustable DALI

# Light output tolerance +/- 10%





























## **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU











### **LAMPTUB 60 SURFACE TRACK**





L61TK112MOOP940D4


LTUB60 TRACK 220 1120 3500 NW OPAL DA BS


### **PHOTOMETRIC DATA:**


L61TK112MOOP940N4 η = 100% Imax = 390 cd/klm UTE: 1,00E + 0,00T CIE: 50 81 97 100 100

















### **LAMPTUB 60 SURFACE TRACK**



# ACCESORIES:

## Assembly



Product code:

L6SUECB



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW



LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.