LAMPTUB 60 SURFACE TRACK

Worktitude for light

L61TK112MOTE940N4

- LTUB60 TK 220 1120 2960 9NW TECH BS



Description:

"""""Luminaire to be installed on a surface-mounted rail, model LAMPTUB 60 TECH by LAMP. Made of 80% recycled aluminium extrusion, with circular section of 60mm and length 1120 mm, with matt black reflector ULTRA COMFORT and optics for light distribution control and low glare UGR<16. Model for MID-POWER LED, with colour temperature 4000K and CRI90. Built-in electronic wiring. With IP20, IK07 degree of protection. Insulation class II. Photobiological safety group 0. Lifetime:50000 L90 B10 Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette. Compatible with Lamp Nomadic system. "" "



Finish: Palette BE SOCIAL - 4 TEXTURED

Dimensions: 1.120 x 67 x 80 mm

Installation: Suspended

TECHNICAL SPECIFICATIONS:

 Light output:
 1.760 lm
 °K:
 4000

 Plum:
 17,8W
 CRI:
 90

 Efficacy:
 98,9 lm/w
 R9:
 85

 UGR:
 <16</td>
 MacAdam:
 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L90 B10 (Ta=25°C)

Power: 14W

Light output tolerance +/- 10%

CUSTOM MADE OPTIONS:



















Gear:

Electronic

LAMPTUB 60 SURFACE TRACK




L61TK112MOTE940N4


LTUB60 TK 220 1120 2960 9NW TECH BS


PHOTOMETRIC DATA:


L61TK112MOTE940N4 η = 100% Imax = 1333 cd/klm UTE:


CIE: 98 100 100 100 100




















LAMPTUB 60 SURFACE TRACK



ACCESORIES:

Assembly



Product code:

L6SUECB



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW



LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.