### **LAMPTUB 60 SURFACE TRACK**



### L61TK168LOOC927NW

### LTUB60 TRACK 220 1680 2500 VWW COMF WH




### Description:

Lamptub 60 model from LAMP to be installed on a surface-mounted rail. Made of recycled aluminium extrusion with circular section of 60mm and length of 1680mm, an opal comfort diffuser made of a translucent polycarbonate diffuser and an optical film to achieve a controlled light distribution and low UGR<19. Model for MID-POWER LED, with colour temperature 2700K with CRI90. Built-in electronic ON/OFF control gear. With IP20, IK07 degree of protection. Insulation class II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.

Finish: Matte white RAL 9010

1.687 x 67 x 112 mm Dimensions: Weight: 3.780 g



### Installation: 3-Circuit track

### **TECHNICAL SPECIFICATIONS:**

Light output: 1.327 lm °K: 2700 Plum: 16,9W CRI: 90 Efficacy: 78,5 lm/w R9: 57 UGR: MacAdam: 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L90 B10 (Ta=25°C) Gear: Electronic

14.9W Power:

### Light output tolerance +/- 10%

































## **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU













### **LAMPTUB 60 SURFACE TRACK**




L61TK168LOOC927NW


### LTUB60 TRACK 220 1680 2500 VWW COMF WH


### **PHOTOMETRIC DATA:**


L61TK168LOOC927NW  $\eta$  = 100% Imax = 665 cd/klm UTE: 1,00C


CIE: 66 90 99 100 100




















## **LAMPTUB 60 SURFACE TRACK**



# ACCESORIES:

## Assembly



Product code:

L6SUECB



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW



LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.