LAMPTUB 60 SURFACE TRACK



L61TK168MOOP930NB




LTUB60 TRACK 220 1680 4900 WW OPAL BK

Description:

Lamptub 60 model from LAMP to be installed on a surface-mounted rail. Made of recycled aluminium extrusion with circular section of 60mm and length of 1680mm, with opal polycarbonate diffuser. Model for MID-POWER LED, with colour temperature 3000K with CRI90. Built-in electronic ON/OFF control gear. With IP20, IK07 degree of protection. Insulation class II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.

Finish: Matte black RAL 9011

1.687 x 67 x 112 mm Dimensions: Weight: 3.780 g



Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output: 3.089 Im °K: 3000 Plum: 33,8W CRI: 90 Efficacy: 91,4 lm/w 64 R9: Type: MID POWER LED MacAdam: 3

LED Lifetime: 50.000 L90 B10 (Ta=25°C) Power Supply: 220-240V 50/60Hz

Gear: Power: 30.3W Electronic

Light output tolerance +/- 10%



















CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU













LAMPTUB 60 SURFACE TRACK





L61TK168MOOP930NB


LTUB60 TRACK 220 1680 4900 WW OPAL BK


PHOTOMETRIC DATA:


L61TK168MOOP930NB η = 100% lmax = 390 cd/klmUTE: 1,00E + 0,00T CIE: 50 81 97 100 100















LAMPTUB 60 SURFACE TRACK



ACCESORIES:

Assembly



Product code:

L6SUECB



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW



LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.