Product datasheet

LUP

LW1110DI40SP40NB



LUP WALL Ø110 DIR/INDIR 4000 NW SP BK.

Description:

Apply to attach to the wall. Model LUP WALL Ø110 DIR/INDIR 4000 NW SP BK., LAMP brand. Body made in extruded recycled aluminum with a rate of 80%., painted in black. Model for LED COB. With 4000K color temperature, CRI 80 and built-in electronic equipment. With direct-indirect Spot optics. With a degree of protection IP65, IK06. Insulation class I. Lifetime: 50.000 L80 B10

Finish: Texturised black RAL 9011

Weight: 2.700 g

Installation: Wall mounted



TECHNICAL SPECIFICATIONS:

Light output: 2.510 lm °K: 4000 Plum: 37,2W CRI: 80 Efficacy: 67,5 lm/w 3 MacAdam:

Type: HIGH POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L70 (Ta=25°C) Gear: Electronic

33W Power:

Light output tolerance +/- 10%































CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU











LUP







PHOTOMETRIC DATA:


LW1110DI40SP40NB


 η = 100%

lmax = 4176 cd/klm

UTE: 0,50T

CIE: 100 100 100 50 100





alpha = 15,7°	H (m)	D (m)	Emax	Emed
\wedge	1	0,28	10416	7099
	2	0,55	2604	1775
	3	0,83	1157	789
	4	1,10	651	444

Data according to regulations 2019/2020/EU and 2019/2015/EU