Product datasheet

MAUI SUSPENDED


MA2SD08SP830NR



MAUI DECO G2 SUS 800 WW SP CR.

Description:

Suspended downlight model MAUI DECO G2 SUS 800 LAMP brand. Made of texturised chrome lacquered injected aluminum. Model for HI-POWER LED with 3000K colour temperature, CRI 80 and control gear included inside the rose. Chromed optical assembly consists of non-flush reflectors for high visual comfort UGR<10. Insulation class II. Lifetime: 50.000 L90 B10. Available finishes: white textured, graphite textured and chrome.



Finish: Gloss grey + Alodine 1500

Weight: 1.800 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output: 597 lm °K: 3000 Plum: 8,2W CRI: 80 Efficacy: 72,8 lm/w 3 MacAdam:

UGR: <10

Type: HIGH POWER LED Gear: Electronic

LED Lifetime: 50.000 L90 B10 (Ta=25°C)

Power: 7.1W

Light output tolerance +/- 10%



















Power Supply:



110-277V 50/60Hz





CUSTOM MADE OPTIONS:













Data according to regulations 2019/2020/EU and 2019/2015/EU

MAUI SUSPENDED



MA2SD08SP830NR

MAUI DECO G2 SUS 800 WW SP CR.

PHOTOMETRIC DATA:

MA2SD08SP830NR η = 100% Imax = 4882 cd/klm UTE: CIE: 102 100 100 100 100

