MAUI SUSPENDED


MA2SD15SP830NR



MAUI DECO G2 SUS 1500 WW SP CR.

Description:

Suspended downlight model MAUI DECO G2 SUS 1500 LAMP brand. Made of texturised chrome lacquered injected aluminum. Model for HI-POWER LED with 3000K colour temperature, CRI 80 and control gear included inside the rose. Chromed optical assembly consists of non-flush reflectors for high visual comfort. Insulation class II. Lifetime: 50.000 L90 B10. Available finishes: white textured, graphite textured and chrome.



Finish: Gloss grey + Alodine 1500

Weight: 1.800 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output: 1.243 lm °K: 3000 Plum: 15,2W CRI: 80 Efficacy: 81,8 lm/w 3 MacAdam:

UGR: <19

Type: HIGH POWER LED Gear: Electronic

LED Lifetime: 50.000 L90 B10 (Ta=25°C)

Power: 14.1W

Light output tolerance +/- 10%

















Power Supply:



110-277V 50/60Hz





CUSTOM MADE OPTIONS:













MAUI SUSPENDED



MA2SD15SP830NR

MAUI DECO G2 SUS 1500 WW SP CR.

PHOTOMETRIC DATA:

MA2SD15SP830NR η = 100% Imax = 3811 cd/klm UTE: CIE: 101 100 100 100 100

