Product datasheet

MAUI SUSPENDED


MA2SU08SP830NB



MAUI G2 SUS 800 WW SP BK.

Description:

Tilting suspended downlight model MAUI G2 SUS 800 LAMP brand. Made of injected aluminum. Model for HI-POWER LED with 3000K colour temperature, CRI 80 and control gear included inside the rose. Chromed optical assembly consists of non-flush reflectors for high visual comfort UGR<10. Insulation class II. Lifetime: 50.000 L90 B10. Available finishes: white, graphite and textured yellow and chrome.



Finish: Texturised graphite RAL 7021

Weight: 640 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output:	597 lm	°K :	3000
Plum:	8,2W	CRI :	80
Efficacy:	72,8 lm/w	MacAdam:	3
UGR:	<10	Power Supply:	110-277V 50/60Hz
Туре:	HIGH POWER LED	Gear:	Electronic
LED Lifetime:	50.000 L90 B10 (Ta=25⁰C)		
Power:	7.1W		

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



Worktitude for light

MAUI SUSPENDED

MA2SU08SP830NB

MAUI G2 SUS 800 WW SP BK.



PHOTOMETRIC DATA :

