Product datasheet

MAUI SUSPENDED


MA2SU08SP830NY



MAUI G2 SUS 800 WW SP YE.

Description:

Tilting suspended downlight model MAUI G2 SUS 800 LAMP brand. Made of injected aluminum. Model for HI-POWER LED with 3000K colour temperature, CRI 80 and control gear included inside the rose. Chromed optical assembly consists of non-flush reflectors for high visual comfort UGR<10. Insulation class II. Lifetime: 50.000 L90 B10. Available finishes: white, graphite and textured yellow and chrome.



Finish: 1021 textured

Weight: 640 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output: 597 lm °K: 3000 Plum: 8,2W CRI: 80 Efficacy: 72,8 lm/w 3 MacAdam:

UGR: <10 Power Supply: 110-277V 50/60Hz

Type: HIGH POWER LED Gear: Electronic

LED Lifetime: 50.000 L90 B10 (Ta=25°C)

Power: 7.1W

Light output tolerance +/- 10%























CUSTOM MADE OPTIONS:













MAUI SUSPENDED



MA2SU08SP830NY

MAUI G2 SUS 800 WW SP YE.

PHOTOMETRIC DATA:

MA2SU08SP830NY η = 100% Imax = 4882 cd/klm UTE: CIE: 102 100 100 100 100

