Product datasheet

MAUI SUSPENDED




MA2SU15SP830NY



MAUI G2 SUS 1500 WW SP YE.

Description:

Tilting suspended downlight model MAUI G2 SUS 1500 LAMP brand. Made of injected aluminum. Model for HI-POWER LED with 3000K colour temperature, CRI 80 and control gear included inside the rose. Chromed optical assembly consists of non-flush reflectors for high visual comfort. Insulation class II. Lifetime: 50.000 L90 B10. Available finishes: white, graphite and textured yellow and chrome.



Finish: 1021 textured

Weight: 640 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

 Light output:
 1.243 lm
 oK:
 3000

 Plum:
 15,2W
 CRI:
 80

 Efficacy:
 81,8 lm/w
 MacAdam:
 3

UGR: <19 **Power Supply**: 110-277V 50/60Hz

Type: HIGH POWER LED Gear: Electronic

LED Lifetime: 50.000 L90 B10 (Ta=25°C)

Power: 14.1W

Light output tolerance +/- 10%























CUSTOM MADE OPTIONS:













MAUI SUSPENDED



MA2SU15SP830NY

MAUI G2 SUS 1500 WW SP YE.

PHOTOMETRIC DATA:

MA2SU15SP830NY η = 100% Imax = 3811 cd/klm UTE: CIE: 101 100 100 100 100

