#### **Product datasheet**


# **SHOT 80**

MC209MF8300A



110 mm

83



#### **Description:**

Outdoor spotlight model SHOT 80 G2 900 NO GEAR, LAMP brand. Made of lacquered aluminium injection with electro coating treatment and tempered glass, stainless steel screws and silicone joints. Model for LED HI-POWER, 3000K colour temperature, CRI 80. With Medium Flood optics. IP65, IK06 protection rating. Insulation class III. Control gear not included. Lifetime: 60. 000 L90B10. BUG Rate: B0 U0 G0, ULOR: 0%. Available finishes: anthracite and textured grey

Finish: Textured anthracite

Weight: 714 g

Installation: Surface

#### **TECHNICAL SPECIFICATIONS:**

Light output:	609 lm	⁰K :	3000		
		CRI :	80		
Туре:	HIGH POWER LED	MacAdam:	3		
LED Lifetime:	60.000 L90 B10 (Ta=25°C)	Power Supply:	700mA DC		
Power:	6W	Gear:	Without gear (requires external gear)		

### Light output tolerance +/- 10%



Worktitude for light

## **SHOT 80**

MC209MF8300A

SHOT 80 G2 900 WW MFL NO GEAR ANT.



MC209MF8300A	180°	alpha = 27,9°	H (m)	D (m)	Emax	Emed
η = 100%		$\land$	1	0,50	1717	1188
Imax = 2828 cd/klm						
UTE: 1,00A	90° 90°		2	0,99	429	297
CIE: 90 98 100 100 100					404	100
			3	1,49	191	132
	Q°		4	1,99	107	74

Worktitude for light

### Product datasheet

# **SHOT 80**

# ACCESORIES :

### Assembly



Product code: MCSPM Description: SHOT 80 G2 ACC. SPIKE

### ACCESORIES :

### Optical



Product code: MCSC82B Description: SHOT 80 G2 ACC. ANTIGLARE SCREEN

## ACCESORIES : Adjustment and control



Product code: 9247940 Description: ACC. DRIVER IP66 700MA 17W



Product code: DRV6721700N

Description: ACC. DRIVER IP67 700MA 21W Worktitude for light