Product datasheet

SHOT 80


MC209MF830NG



SHOT 80 G2 900 WW MFL GR.

Description:

Outdoor spotlight model SHOT 80 G2 900, LAMP brand. Made of lacquered aluminium injection with electro coating treatment and tempered glass, stainless steel screws and silicone joints. Model for LED HI-POWER, 3000K colour temperature, CRI 80 and control gear included. With Medium Flood optics. IP65, IK06 protection rating. Insulation class II. Lifetime: 60. 000 L90B10. BUG Rate: B0 U0 G0, ULOR: 0%. Available finishes: anthracite and textured grey



Finish: Texturised grey

Weight: 1.324 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 609 lm °K: 3000 Plum: 7W CRI: 80 Efficacy: 87 lm/w 3 MacAdam:

Type: HIGH POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 60.000 L90 B10 (Ta=25°C) Gear: Electronic

6W Power:

Light output tolerance +/- 10%















IΡ

65













+34937366800

SHOT 80







PHOTOMETRIC DATA:

MC209MF830NG $\eta = 100\%$ Imax = 2828 cd/klm UTE: 1,00A

CIE: 90 98 100 100 100





alpha = 27,9°	H (m)	D (m)	Emax	Emed
\bigwedge	1	0,50	1717	1188
	2	0,99	429	297
	3	1,49	191	132
	4	1,99	107	74

Product datasheet

SHOT 80



ACCESORIES:

Assembly



Product code: Description:

MCSPM SHOT 80 G2 ACC. SPIKE

ACCESORIES:

Optical



Product code: Description:

MCSC82B SHOT 80 G2 ACC. ANTIGLARE SCREEN