Product datasheet

SHOT 80

MC209MF8400A



110 mm

83



Description:

Outdoor spotlight model SHOT 80 G2 900, LAMP brand. Made of lacquered aluminium injection with electro coating treatment and tempered glass, stainless steel screws and silicone joints. Model for LED HI-POWER, 4000K colour temperature, CRI 80 and control gear included. With Spot optics. IP65, IK06 protection rating. Insulation class II. Lifetime: 60. 000 L90B10. BUG Rate: B0 U0 G0, ULOR: 0%. Available finishes: anthracite and textured grey

Finish: Textured anthracite

Weight: 714 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output:	609 lm	⁰K :	4000		
		CRI :	80		
Туре:	HIGH POWER LED	MacAdam:	3		
LED Lifetime:	60.000 L90 B10 (Ta=25°C)	Power Supply:	700mA DC		
Power:	6W	Gear:	Without gear (requires external gear)		

Light output tolerance +/- 10%



Worktitude for light

SHOT 80

MC209MF8400A

SHOT 80 G2 900 NW MFL NO GEAR ANT.



MC209MF8400A	180°	alpha = 27,9°	H (m)	D (m)	Emax	Emed
η = 100% Imax = 2828 cd/klm		\land	1	0,50	1717	1188
UTE: 1,00A	90° 90°		2	0,99	429	297
CIE: 90 98 100 100 100			3	1,49	191	132
				1,45	101	102
	0 °		4	1,99	107	74

Worktitude for light

Product datasheet

SHOT 80

ACCESORIES :

Assembly



Product code: MCSPM Description: SHOT 80 G2 ACC. SPIKE

ACCESORIES :

Optical



Product code: MCSC82B Description: SHOT 80 G2 ACC. ANTIGLARE SCREEN

ACCESORIES : Adjustment and control



Product code: 9247940 Description: ACC. DRIVER IP66 700MA 17W



Product code: DRV6721700N

Description: ACC. DRIVER IP67 700MA 21W Worktitude for light