
Product datasheet

SHOT 80

MC209MF840NA





SHOT 80 G2 900 NW MFL ANT.

Description:

Outdoor spotlight model SHOT 80 G2 900, LAMP brand. Made of lacquered aluminium injection with electro coating treatment and tempered glass, stainless steel screws and silicone joints. Model for LED HI-POWER, 4000K colour temperature, CRI 80 and control gear included. With Medium Flood optics. IP65, IK06 protection rating. Insulation class II. Lifetime: 60. 000 L90B10. BUG Rate: B0 U0 G0, ULOR: 0%. Available finishes: anthracite and textured grey

Finish: Textured anthracite

Weight: 1.324 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output:	609 lm	⁰K :	4000	
Plum:	7W	CRI :	80	
Efficacy:	87 lm/w	MacAdam:	3	
Туре:	HIGH POWER LED	Power Supply:	220-240V 50/60Hz	
LED Lifetime:	60.000 L90 B10 (Ta=25⁰C)	Gear:	Electronic	
Power:	6W			

Light output tolerance +/- 10%



Worktitude for light

SHOT 80

MC209MF840NA

SHOT 80 G2 900 NW MFL ANT.



MC209MF840NA	180°	alpha = 27,9°	H (m)	D (m)	Emax	Emed
$\eta = 100\%$		\land	1	0,50	1717	1188
lmax = 2828 cd/klm UTE: 1,00A	90° 90°		2	0.99	429	297
CIE: 90 98 100 100 100				0,00	420	201
			3	1,49	191	132
	Q°		4	1,99	107	74



Product datasheet

SHOT 80

ACCESORIES :

Assembly



Product code: MCSPM Description: SHOT 80 G2 ACC. SPIKE

ACCESORIES :

Optical



Product code: MCSC82B Description: SHOT 80 G2 ACC. ANTIGLARE SCREEN Worktitude for light