Product datasheet

SHOT 80



MC209SP8400G




SHOT 80 G2 900 NW SP NO GEAR GR.

Description:

Outdoor spotlight model SHOT 80 G2 900 NO GEAR, LAMP brand. Made of lacquered aluminium injection with electro coating treatment and tempered glass, stainless steel screws and silicone joints. Model for LÉD HI-POWER, 4000K colour temperature, CRI 80. With Spot optics. IP65, IK06 protection rating. Insulation class III. Control gear not included. Lifetime: 60. 000 L90B10. BUG Rate: B0 U0 G0, ULOR: 0%. Available finishes: anthracite and textured grey

Finish: Texturised grey

Weight: 714 g



Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 720 lm °K: 4000

> CRI: 80

Type: HIGH POWER LED 3 MacAdam:

LED Lifetime: 60.000 L90 B10 (Ta=25°C) Power Supply: 700mA DC

Power: 6W Gear: Without gear (requires external gear)

Light output tolerance +/- 10%



















IΡ

65











LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es

+34937366800

SHOT 80






SHOT 80 G2 900 NW SP NO GEAR GR.

PHOTOMETRIC DATA:

MC209SP8400G $_{\eta}$ = 100% $_{lmax}$ = 6135 cd/klm UTE: CIE: 99 100 100 100 100



alpha = 19,9°	H (m)	D (m)	Emax	Emed
\wedge	1	0,35	4402	3175
	2	0,70	1101	794
	3	1,05	489	353
	4	1,41	275	198

Product datasheet

SHOT 80



ACCESORIES:

Assembly



Product code: Description:

MCSPM SHOT 80 G2 ACC. SPIKE

ACCESORIES:

Optical



Product code: Description:

MCSC82B SHOT 80 G2 ACC. ANTIGLARE SCREEN

ACCESORIES:

Adjustment and control



Product code: Description:

9247940 ACC. DRIVER IP66 700MA 17W



Product code:

DRV6721700N

Description:

ACC. DRIVER IP67 700MA 21W