Product datasheet

SHOT 80


MC209SP840NA



SHOT 80 G2 900 NW SP ANT.

Description:

Outdoor spotlight model SHOT 80 G2 900, LAMP brand. Made of lacquered aluminium injection with electro coating treatment and tempered glass, stainless steel screws and silicone joints. Model for LED HI-POWER, 4000K colour temperature, CRI 80 and control gear included. With Spot optics. IP65, IK06 protection rating. Insulation class II. Lifetime: 60. 000 L90B10. BUG Rate: B0 U0 G0, ULOR: 0%. Available finishes: anthracite and textured grey



Finish: Textured anthracite

Weight: 1.324 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 720 lm °K: 4000 Plum: 7W CRI: 80 Efficacy: 103 lm/w 3 MacAdam:

Type: HIGH POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 60.000 L90 B10 (Ta=25°C) Gear: Electronic

6W Power:

Light output tolerance +/- 10%










































Data according to regulations 2019/2020/EU and 2019/2015/EU


SHOT 80








PHOTOMETRIC DATA:





alpha = 19,9°	H (m)	D (m)	Emax	Emed
\wedge	1	0,35	4402	3175
	2	0,70	1101	794
	3	1,05	489	353
	4	1,41	275	198

Product datasheet

SHOT 80



ACCESORIES:

Assembly



Product code: Description:

MCSPM SHOT 80 G2 ACC. SPIKE

ACCESORIES:

Optical



Product code: Description:

MCSC82B SHOT 80 G2 ACC. ANTIGLARE SCREEN