Product datasheet

MODULAR CUSTOM

MCA1903035PR830DW




MOD CUSTOM AIR 90X30 3400 WW PR DA WH

Description:

LAMP MODULAR CUSTOM AIR recessed 900X300 format. Return air-specific model of the family. Slots for air extraction with return to plenum with a capacity of 40l/sg - 144m3/h. Custom option: adaptable to any installation, technical ceiling, finish or technical aspects by the needs of the project. Made of steel, prismatic diffuser of translucent polycarbonate and an optical film to control light distribution and reduce glare UGR <19. Model for MID-POWER LED, 3000K colour temperature and IRC 80. Control DALI gear included. With a protection rating of IP23. Insulation class I. Photobiological safety group 0. Lifetime: 50.000 L80 B10.

Finish:Matte Traffic white RAL 9016Dimensions:900 x 300 x 72,8 mm




Installation: Recessed

TECHNICAL SPECIFICATIONS:

| Light output: | 2.553 lm | °K : | 3000 |
|---------------|--------------------------|---------------|------------------|
| Plum: | 31W | CRI : | 80 |
| Efficacy: | 82,4 lm/w | MacAdam: | 3 |
| UGR: | <19 | Power Supply: | 220-240V 50/60Hz |
| Туре: | MID POWER | Gear: | Adjustable DALI |
| LED Lifetime: | 50.000 L80 B10 (Ta=25⁰C) | | |
| Power: | 27W | | |

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



Worktitude for light

MODULAR CUSTOM

MCA1903035PR830DW

MOD CUSTOM AIR 90X30 3400 WW PR DA WH



PHOTOMETRIC DATA :

