# **MODULAR LIGHTAIR**

#### MCA1903035PR830NW



#### MOD CUSTOM AIR 90X30 3400 WW PR WH

#### Description:

LAMP MODULAR CUSTOM AIR recessed 900X300 format. Return air-specific model of the family. Slots for air extraction with return to plenum with a capacity of 40l/sg - 144m3/h. Custom option: adaptable to any installation, technical ceiling, finish or technical aspects by the needs of the project. Made of steel, prismatic diffuser of translucent polycarbonate and an optical film to control light distribution and reduce glare UGR <19. Model for MID-POWER LED, 3000K colour temperature and IRC 80. Control gear included. With a protection rating of IP23. Insulation class I. Photobiological safety group 0. Lifetime: 50.000 L80 B10.



Finish: Matte Traffic white RAL 9016 900 x 300 x 72,8 mm Dimensions:

Installation: Recessed

#### **TECHNICAL SPECIFICATIONS:**

Light output: 2.553 lm °K: 3000 Plum: 31W CRI: 80 Efficacy: 82,4 lm/w 3 MacAdam:

UGR: <19 MID POWER

LED Lifetime: 50.000 L80 B10 (Ta=25°C)

Power:

# Light output tolerance +/- 10%



Type:







































Data according to regulations 2019/2020/EU and 2019/2015/EU











Power Supply:

Gear:

220-240V 50/60Hz

Electronic

# **MODULAR LIGHTAIR**



MCA1903035PR830NW

# MOD CUSTOM AIR 90X30 3400 WW PR WH

### **PHOTOMETRIC DATA:**

MCA1903035PR830NW  $\eta = 100\%$   $Imax = 519 \ cd/kIm$  UTE: 1,00C

CIE: 65 92 99 100 100







