Product datasheet

MODULAR LIGHTAIR

MCA1903035PR840DW



MOD CUSTOM AIR 90X30 3400 NW PR DA WH

Description:

LAMP MODULAR CUSTOM AIR recessed 900X300 format. Return air-specific model of the family. Slots for air extraction with return to plenum with a capacity of 40l/sg - 144m3/h. Custom option: adaptable to any installation, technical ceiling, finish or technical aspects by the needs of the project. Made of steel, prismatic diffuser of translucent polycarbonate and an optical film to control light distribution and reduce glare UGR <19. Model for MID-POWER LED, 4000Kcolour temperature and IRC 80. Control DALI gear included. With a protection rating of IP23. Insulation class I. Photobiological safety group 0. Lifetime: 50.000 L80 B10.

-7	4	900	-
l	2		300
	5		2 (Q


Finish:Matte white RAL 9010Dimensions:900 x 300 x 72,8 mm

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	3.004 lm	٥К:	4000
Plum:	31W	CRI :	80
Efficacy:	96,9 lm/w	MacAdam:	3
UGR:	<19	Power Supply:	220-240V 50/60Hz
Туре:	MID POWER	Gear:	Adjustable DALI
LED Lifetime:	50.000 L80 B10 (Ta=25⁰C)		
Power:	27W		

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



Worktitude for light

MODULAR LIGHTAIR

MCA1903035PR840DW

MOD CUSTOM AIR 90X30 3400 NW PR DA WH



PHOTOMETRIC DATA :

