Product datasheet

MUN DARK


MD1SF2000165830NW



MUN DARK SUR Ø200 IP65 WW WH

Description:

LAMP wall mounted indirect fixture model MUN DARK SUR Ø200 IP65. Manufactured of aluminium with Opal polycarbonate diffusor. Model for LED MID-POWER, colour temperature 3000K and IRC80. Electronic ON OFF gear included. IP65, IK08 ratings. Insulation Class I. Photobiological safety group 0. LED life time: 50.000 L90 B10. Available finishes: White and textured graphite.



Finish: Matte white RAL 9010

Weight: 1.350 g

Installation: Wall mounted

TECHNICAL SPECIFICATIONS:

Light output: 630 lm °K: 3000 Plum: 9,1W CRI: 80 Efficacy: 69,2 lm/w 3 MacAdam:

Type: MID POWER Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L90B10 (Ta=25°C) Gear: Electronic

8W Power:

Light output tolerance +/- 10%





















CUSTOM MADE OPTIONS:










Data according to regulations 2019/2020/EU and 2019/2015/EU

MUN DARK







PHOTOMETRIC DATA:

MD1SF2000165830NW η = 100% Imax = 509 cd/klm UTE: 0,95D + 0,06T CIE: 51 79 94 94 100

