#### **Product datasheet**

#### **MUN LIGHT**

## LAMP Worktitude for light

#### ML1300SF10830NB



#### MUN LIGHT SUR Ø300 1000 WW GRH.

#### Description:

Round for ceiling mounting downlight model MUN LIGHT SUR Ø300, LAMP brand. Made of textured graphite painted extruded aluminum and with methacrylate opal diffuser. Model for LED LOW-POWER with 3000K color temperature, CRI 80 and control gear included. IP20 protection rating. Insulation class I. Lifetime: 50.000 L80 B10. Available finishes: White and textured graphite.



Finish: Texturised matte graphite RAL 7021

Weight: 1.938 g

Installation: Surface

#### **TECHNICAL SPECIFICATIONS:**

 Light output:
 716 lm
 °K:
 3000

 Plum:
 9,3W
 CRI:
 80

 Efficacy:
 77 lm/w
 MacAdam:
 <3</td>

Type: LOW POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 8W

#### Light output tolerance +/- 10%



















# CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU












### **MUN LIGHT**




ML1300SF10830NB

#### MUN LIGHT SUR Ø300 1000 WW GRH.

#### **PHOTOMETRIC DATA:**





alpha = 115,2°	H (m)	D (m)	Emax	Emed
	1	3,15	245	70
	2	6,30	61	17
	3	9,45	27	8
	4	12,59	15	4