Product datasheet

MUN LIGHT

Worktitude for light

ML1300SF10840NW



MUN LIGHT SUR Ø300 1000 NW WH.

Description:

Round for ceiling mounting downlight model MUN LIGHT SUR Ø300, LAMP brand. Made of textured white painted extruded aluminum and with methacrylate opal diffuser. Model for LED LOW-POWER with 4000K color temperature, CRI 80 and control gear included. IP20 protection rating. Insulation class I. Lifetime: 50.000 L80 B10. Available finishes: White and textured graphite.



Finish: Texturised matte white RAL 9016

Weight: 1.938 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

 Light output:
 761 lm
 °K:
 4000

 Plum:
 9,3W
 CRI:
 80

 Efficacy:
 81,8 lm/w
 MacAdam:
 <3</td>

Type: LOW POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 8W

Light output tolerance +/- 10%



CLASE

IK 08













CUSTOM MADE OPTIONS:


















MUN LIGHT




ML1300SF10840NW

MUN LIGHT SUR Ø300 1000 NW WH.

PHOTOMETRIC DATA:





alpha = 115,2°	H (m)	D (m)	Emax	Emed
	1	3,15	260	74
	2	6,30	65	19
	3	9,45	29	8
	4	12,59	16	5