Product datasheet

MUN LIGHT

Worktitude for light

ML1300SF30830NB



MUN LIGHT SUR Ø300 3000 WW GRH.

Description:

Round for ceiling mounting downlight model MUN LIGHT SUR Ø300, LAMP brand. Made of textured graphite painted extruded aluminum and with methacrylate opal diffuser. Model for LED MID-POWER with 3000K color temperature, CRI 80 and control gear included. IP20 protection rating. Insulation class I. Lifetime: 50.000 L80 B10. Available finishes: White and textured graphite.



Finish: Texturised matte graphite RAL 7021

Weight: 1.938 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

 Light output:
 1.492 lm
 °K:
 3000

 Plum:
 26,2W
 CRI:
 80

 Efficacy:
 56,9 lm/w
 MacAdam:
 <3</td>

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 22W

Light output tolerance +/- 10%

















CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU












MUN LIGHT




ML1300SF30830NB

MUN LIGHT SUR Ø300 3000 WW GRH.

PHOTOMETRIC DATA:





alpha = 113,5°	H (m)	D (m)	Emax	Emed
	1	3,05	518	152
	2	6,10	130	38
	3	9,15	58	17
	4	12,20	32	10