Product datasheet

MUN LIGHT

ML1300SF30830NW



MUN LIGHT SUR Ø300 3000 WW WH.

Description:

Round for ceiling mounting downlight model MUN LIGHT SUR $\emptyset 300$, LAMP brand. Made of textured white painted extruded aluminum and with methacrylate opal diffuser. Model for LED MID-POWER with 3000K color temperature, CRI 80 and control gear included. IP20 protection rating. Insulation class I. Lifetime: 50.000 L80 B10. Available finishes: White and textured graphite.



Finish: Texturised matte white RAL 9016

Weight: 1.938 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 1.613 lm °K: 3000 Plum: 26,2W CRI: 80 Efficacy: 61,6 lm/w MacAdam: <3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

22W Power:

Light output tolerance +/- 10%



















CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU












MUN LIGHT




ML1300SF30830NW

MUN LIGHT SUR Ø300 3000 WW WH.

PHOTOMETRIC DATA:





alpha = 113,9°	H (m)	D (m)	Emax	Emed
	1	3,07	558	163
	2	6,15	140	41
	3	9,22	62	18
	4	12,30	35	10