Product datasheet

MUN LIGHT

ML1300SF30830NW





MUN LIGHT SUR Ø300 3000 WW WH.

Description:

Round for ceiling mounting downlight model MUN LIGHT SUR Ø300, LAMP brand. Made of textured white painted extruded aluminum and with methacrylate opal diffuser. Model for LED MID-POWER with 3000K color temperature, CRI 80 and control gear included. IP20 protection rating. Insulation class I. Lifetime: 50.000 L80 B10. Available finishes: White and textured graphite.



Finish: Texturised matte white RAL 9016 Weight: 1.938 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output:	1.613 lm	⁰К:	3000	
Plum:	26,2W	CRI :	80	
Efficacy:	61,6 lm/w	MacAdam:	<3	
Туре:	MID POWER LED	Power Supply:	220-240V 50/60Hz	
LED Lifetime:	50.000 L80 B10 (Ta=25°C)	Gear:	Electronic	
Power:	22W			

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



Worktitude for light

MUN LIGHT

ML1300SF30830NW

MUN LIGHT SUR Ø300 3000 WW WH.



PHOTOMETRIC DATA :

10541040	180°	alpha = 113,9°	H (m)	D (m)	Emax	Emed
$\eta = 100\%$			1	3,07	558	163
lmax = 346 cd/klm UTE: 1,00E + 0,00T	90° 90°		2	6,15	140	41
CIE: 47 79 96 100 100	30 30		2	0,10	140	
			3	9,22	62	18
	00		4	12,30	35	10