#### **Product datasheet**

#### **MUN LIGHT**

#### ML1300SU10830NB



## MUN LIGHT SUS Ø300 1000 WW GRH.

#### Description:

Round suspended downlight model MUN LIGHT SUS Ø300, LAMP brand. Made of textured graphite painted extruded aluminum and with methacrylate opal diffuser. Model for LED LOW-POWER with 3000K color temperature, CRI 80 and control gear included. IP20 protection rating. Insulation class I. Lifetime: 50.000 L80 B10. Available finishes: White and textured graphite.



Finish: Texturised matte graphite RAL 7021

Weight: 2.258 g

Installation: Suspended

#### **TECHNICAL SPECIFICATIONS:**

Light output: 716 lm °K: 3000 Plum: 9,3W CRI: 80 Efficacy: 77 lm/w MacAdam: <3

Type: LOW POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

8W Power:

### Light output tolerance +/- 10%



CLASE

IK 80

























## **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU












# **MUN LIGHT**




ML1300SU10830NB

## MUN LIGHT SUS Ø300 1000 WW GRH.

### **PHOTOMETRIC DATA:**





alpha = 115,2°	H (m)	D (m)	Emax	Emed
	1	3,15	245	70
	2	6,30	61	17
	3	9,45	27	8
	4	12,59	15	4