#### **Product datasheet**

#### **MUN LIGHT**

#### ML1300SU10840NW



# MUN LIGHT SUS Ø300 1000 NW WH.

#### Description:

Round suspended downlight model MUN LIGHT SUS Ø300, LAMP brand. Made of textured white painted extruded aluminum and with methacrylate opal diffuser. Model for LED LOW-POWER with 4000K color temperature, CRI 80 and control gear included. IP20 protection rating. Insulation class I. Lifetime: 50.000 L80 B10. Available finishes: White and textured graphite.



Finish: Texturised matte white RAL 9016

Weight: 2.258 g

Installation: Suspended

#### **TECHNICAL SPECIFICATIONS:**

Light output: 761 lm °K: 4000 Plum: 9,3W CRI: 80 Efficacy: 81,8 lm/w MacAdam: <3

Type: LOW POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

8W Power:

## Light output tolerance +/- 10%



















## **CUSTOM MADE OPTIONS:**


















## **MUN LIGHT**




ML1300SU10840NW

## MUN LIGHT SUS Ø300 1000 NW WH.

## **PHOTOMETRIC DATA:**





alpha = 115,2°	H (m)	D (m)	Emax	Emed
	1	3,15	260	74
	2	6,30	65	19
	3	9,45	29	8
	4	12,59	16	5