Product datasheet

MUN LIGHT

ML1300SU30830NB



MUN LIGHT SUS Ø300 3000 WW GRH.

Description:

Round suspended downlight model MUN LIGHT SUS Ø300, LAMP brand. Made of textured graphite painted extruded aluminum and with methacrylate opal diffuser. Model for LED MID-POWER with 3000K color temperature, CRI 80 and control gear included. IP20 protection rating. Insulation class I. Lifetime: 50.000 L80 B10. Available finishes: White and textured graphite.



Finish: Texturised matte graphite RAL 7021

Weight: 2.258 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output: 1.492 lm °K: 3000 Plum: 26,2W CRI: 80 Efficacy: 56,9 lm/w MacAdam: <3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

22W Power:

Light output tolerance +/- 10%



















CUSTOM MADE OPTIONS:




















MUN LIGHT




ML1300SU30830NB

MUN LIGHT SUS Ø300 3000 WW GRH.

PHOTOMETRIC DATA:





alpha = 113,5°	H (m)	D (m)	Emax	Emed
	1	3,05	518	152
	2	6,10	130	38
	3	9,15	58	17
	4	12,20	32	10