#### **Product datasheet**

#### **MUN LIGHT**

# Worktitude for light

#### ML1300SU30830NW

### MUN LIGHT SUS Ø300 3000 WW WH.

#### Description:

Round suspended downlight model MUN LIGHT SUS Ø300, LAMP brand. Made of textured white painted extruded aluminum and with methacrylate opal diffuser. Model for LED MID-POWER with 3000K color temperature, CRI 80 and control gear included. IP20 protection rating. Insulation class I. Lifetime: 50.000 L80 B10. Available finishes: White and textured graphite.



Finish: Texturised matte white RAL 9016

Weight: 2.258 g

Installation: Suspended

#### **TECHNICAL SPECIFICATIONS:**

 Light output:
 1.613 lm
 °K:
 3000

 Plum:
 26,2W
 CRI:
 80

 Efficacy:
 61,6 lm/w
 MacAdam:
 <3</td>

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 22W

#### Light output tolerance +/- 10%



CLASE

IK 08



**LED** 3000°K









## **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU












# **MUN LIGHT**





#### **PHOTOMETRIC DATA:**

10541080  $\eta$  = 100% Imax = 346 cd/klm UTE: 1,00E + 0,00T CIE: 47 79 96 100 100



MUN LIGHT SUS Ø300 3000 WW WH.

alpha = 113,9°		

H (m)	D (m)	Emax	Emed
1	3,07	558	163
2	6,15	140	41
3	9,22	62	18
4	12,30	35	10