Product datasheet

MUN LIGHT

ML1300SU30840NW



MUN LIGHT SUS Ø300 3000 NW WH.

Description:

Round suspeded downlight modelMUN LIGHT SUS $\emptyset 300$, LAMP brand. Made of textured white painted extruded aluminum and with methacrylate opal diffuser. Model for LED MID-POWER with 4000K color temperature, CRI 80 and control gear included. IP20 protection rating. Insulation class I. Lifetime: 50.000 L80 B10. Available finishes: White and textured graphite.



Finish: Texturised matte white RAL 9016

Weight: 2.258 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output: 1.613 lm °K: 4000 Plum: 26,2W CRI: 80 Efficacy: 61,6 lm/w MacAdam: <3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

22W Power:

Light output tolerance +/- 10%



CLASE

IK 80













CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU












MUN LIGHT




ML1300SU30840NW

MUN LIGHT SUS Ø300 3000 NW WH.

PHOTOMETRIC DATA:





alpha = 113,9°	H (m)	D (m)	Emax	Emed
	1	3,07	558	163
	2	6,15	140	41
	3	9,22	62	18
	4	12,30	35	10